

TrakkaCam[®] TC-300-UC



A NEW-GENERATION OF COMPACT LOW COST MULTI SENSOR SURVEILLANCE SYSTEMS

Ideally suited for air, maritime and land missions including law enforcement, search and rescue, civil protection, military ISR and force protection, manned and unmanned platforms and installations.

TRAKKA SYSTEMS TC SERIES

The new TC series from Trakka Systems features advanced technology in an ergonomic industrial design that sets new standards for compact, high-performance, multispectral imaging in a non-ITAR single-LRU configuration.

The EO/IR sensors are augmented with sophisticated image processing, allowing users to see through conditions such as fog, haze, low light, and total darkness. Image blending provides the ability to exploit imagery from the different sensors and extract details that would otherwise go undetected by a single sensor. A host of image processing features to improve operator performance and reduce workload, such as Moving Target Detection (MTI), are embedded right into the system.

The TC-300-UC has enhanced interfaces that provide easy integration with 3rd party equipment. Unlike competing imagers, the TC-300-UC integrates advanced features like dual-stream H.264 video with KLV metadata over ethernet right into the system, removing the need for external encoders and enabling simplified integration with Moving Map and datalink systems.

The TC-300-UC enables operators and command centers to share mission-critical information in real-time while providing enhanced situational awareness via augmented reality overlays or pure synthetic views.

KEY BENEFITS

- Cost effective solution for shorter range missions
- Available with a full suite of 7 payload options: (IR, HDTV, LRF, LP, LI, A/T, IMU/GPS)
- Continuous optical zoom on all imaging channels for maximum situational awareness
- The advanced real-time digital HD image processing engine is embedded in gimbal and requires no additional electronics unit
- Moving Target Detection (MTI) embedded directly into the system
- High performance 4-axis active gyro stabilization with integrated 6-axis passive isolation for superior image stabilization
- Fully integrated IMU/INS providing Geo Location and Geo Hold, with easy Moving Maps integration
- Ergonomic and compact design provides flexible platform and installation options
- Compact Single-LRU configuration is easy to install, integrate and requires no junction box
- Non-ITAR exportable product
- RTCA DO-160 Tested for Environmental Electromagnetic and Mechanical compliance



TC-300-UC

GIMBAL SPECIFICATIONS

Weight	~20 kg (44 lb)
Diameter	300mm (11.8")
Azimuth	Continuous Azimuth
Elevation	+20° to -120° Elevation (+90 Stow)
Stabilization	4 axis, active gyro-stabilization with integrated 6 axis passive isolation

THERMAL IMAGER

Type	8-12µm LWIR array
Resolution	640x512
Fields of View	29° to 5.9° Continuous Zoom
Sensor Type	Un-Cooled

HDTV CAMERA

Type	HD CMOS Global Shutter
Resolution	2.37 MPixels (1080p)
Fields of View	35° to 1.3° continuous zoom

LASER RANGE FINDER (OPTIONAL)

Wavelength	1535 nm, Eye-safe
Range	12km
Repetition Rate	1 Hz or Single-Shot Modes

LASER POINTER (OPTIONAL)

Type	Class 3B
Wavelength	830nm
Output Power	80mW

LASER ILLUMINATOR (OPTIONAL)

Type	Class 3B
Wavelength	860nm
Output Power	450mW

ELECTRICAL REQUIREMENTS

Max power	320W Maximum Power
Steady State Power	100W Steady State
Input Voltage	22-36V Wide-Range Input Voltage

OPTIONS

Interface Types	SMPTE HD video outputs and H.264 over Ethernet (MISB 0601.7 Compliant), RS422, RS232
Functional Interfaces & Features	Auto Tracking, Geo-Location with integrated IMU/INS, Interface to Aircraft INS/GPS, Metadata, Moving Maps & Augmented Reality, Remote Control, Search-light Slaving, Radar Slaving, Data Links & Video Downlinks

ENVIRONMENTAL

Standards	MIL-STD 461, MIL-STD 810, RTCA DO-160
------------------	---------------------------------------



FEATURES

- Moving Target Detection (option)
- Object Tracking / Scene Tracking Modes (option)
- Image Blending (option)
- Digital Contrast Enhancement
- Local Area Contrast Processing
- Edge Sharpening
- Image Noise Reduction
- Picture in Picture / Split screen
- Graphical On-Screen Display for Intuitive Operation



Trakka Corp Pty Ltd
23 Kilpa Road, Moorabbin
Victoria 3189 Australia
Phone: +61 3 9553 3000

Trakka Systems AB
Stationsvägen 46
640 43 Ärla Sweden
Phone: +46 16 708 60

Trakka USA LLC
4725 Lena Road, Unit 103
Bradenton Florida 34211, USA
Phone: +1 941 500-5158

trakkasystems.com
info@trakkasystems.com